albatros Watt = Kcal/h \div 0,860 $Kcal/h = Watt \times 0,860$

Price for items with White RAL 9010 finish and standard connectors, VAT and transport costs not included For correction factors different to ΔT 50°C see page 209

To help you properly fill out the code relative to the item requested see code examples on page 5

The ALBATROS model is created with 14 mm horizontal curved steel elements.

To identify the radiator model to be ordered, proceed as follows:

Identify and specify the code (e.g. AL), the width (e.g. 150), the number of elements (e.g. 20 equal to a height of 55,5 cm), the connector (e.g. OB1), the support (e.g. ST), and the colour (e.g. white RAL 9010). Therefore, in this example the complete code is:

AL# 150 020 0B1 ST 9010 D9005 (see code example on page 5)

ADDITIONAL COLOUR AND FINISH CHARGE (see new colour chart)

The additional charges are calculated on the base price of RAL 9010 for the coloured versions and on the base price of Glossy Chrome for the plated finishes.

C0 Category without any additional charge (RAL 9010)

C1 Category +10% C2 Category +15% C3 Category +20% RAL colours not included in the colour chart +30%

request feasibility and cost estimate Colours according to samples

PLATED finishes

G0 Category without any additional charge (Glossy Chrome) G1 Category without any additional charge (Satin-finish Nickel)

G5 Category +50% (14kt Gold) +60% (24kt Gold) **G6 Category**

BRACKET SUPPORTS

The ALBATROS model cannot be supplied with bracket supports.

PACKING


The cardboard packing box is included in the price of sale of the products, and for the ALBATROS model it contains the complete wall fixing kit and the manual vent valve.


The curving of Albatros elements are not precisely identical because due to manual processing there could be some difference in size (± 0.5 cm).

The ALBATROS model is supplied exclusively with specifically modified "OB1" connectors.

This model cannot be installed vertically, but only horizontally.

Model	N° elements	H (cm)	L (cm)	Inter-axis (cm)	Watts ∆T 50°C Coloured version	Watts ∆T 50°C Chrome plated version	Category C0 RAL 9010 (€)	Category C1 (€)	Category C3 (€)	Chrome plated G0 (€)
AL#150010	10	31,5	149,0	103,5	467	420				
AL#150012	12	36,3	149,0	103,5	565	509				
AL#150014	14	41,1	149,0	103,5	668	602				
AL#150016	16	45,9	149,0	103,5	772	695				
AL#150018	18	50,7	149,0	103,5	874	786				
AL#150020	20	55,5	149,0	103,5	974	877	Ì			
AL#150022	22	60,3	149,0	103,5	1075	967				
AL#150024	24	65,1	149,0	103,5	1173	1055				
AL#150026	26	69,9	149,0	103,5	1269	-				_
AL#150028	28	74,7	149,0	103,5	1365	_				_
AL#150030	30	79,5	149,0	103,5	1459	_				_





albatros

Watt = Kcal/h ÷ 0,860
Kcal/h = Watt x 0,860

Price for items with White RAL 9010 finish and standard connectors, VAT and transport costs not included For correction factors different to ΔT 50°C see page 209

To help you properly fill out the code relative to the item requested see code examples on page 5

The ALBATROS model is created with 14 mm horizontal curved steel elements.

To identify the radiator model to be ordered, proceed as follows:

Identify and specify the code (e.g. AL), the width (e.g. 200), the number of elements (e.g. 20 equal to a height of 55,5 cm), the connector (e.g. 0B1), the support (e.g. ST), and the colour (e.g. white RAL 9010).

Therefore, in this example the complete code is:

AL# 200 020 0B1 ST 9010 D9005 (see code example on page 5)

For the black finish models the decorative central element is supplied in Matte Black or Grey Chrome. On request ALBATROS can also be supplied without the decorative element.

ADDITIONAL COLOUR AND FINISH CHARGE (see new colour chart)

The additional charges are calculated on the base price of RAL 9010 for the coloured versions and on the base price of Glossy Chrome for the plated finishes.

C0 Category without any additional charge (RAL 9010)

C1 Category +10%
C2 Category +15%
C3 Category +20%
RAL colours not included in the colour chart +30%

Colours according to samples request feasibility and cost estimate

PLATED finishes

G0 Category without any additional charge (Glossy Chrome)
G1 Category without any additional charge (Satin-finish Nickel)

G5 Category +50% (14kt Gold) G6 Category +60% (24kt Gold)

BRACKET SUPPORTS

The ALBATROS model cannot be supplied with bracket supports.

PACKING

The cardboard packing box is included in the price of sale of the products, and for the ALBATROS model it contains the complete wall fixing kit and the manual vent valve.

NOTES

The curving of Albatros elements are not precisely identical because due to manual processing there could be some difference in size (\pm 0.5 cm).

CONNECTORS

The ALBATROS model is supplied exclusively with specifically modified "0B1" connectors.

This model cannot be installed vertically, but only horizontally.

Model	N° elements	H (cm)	L (cm)	Inter-axis (cm)	Watts ∆T 50°C Coloured version	Watts ∆T 50°C Chrome plated version	Category C0 RAL 9010 (€)	Category C1 (€)	Category C3 (€)	Chrome plated G0 (€)
AL#200010	10	31,5	198,0	141,0	622	559				
AL#200012	12	36,3	198,0	141,0	754	676				
AL#200014	14	41,1	198,0	141,0	892	803				
AL#200016	16	45,9	198,0	141,0	1029	926				
AL#200018	18	50,7	198,0	141,0	1165	1048				
AL#200020	20	55,5	198,0	141,0	1299	1168				
AL#200022	22	60,3	198,0	141,0	1433	1289				
AL#200024	24	65,1	198,0	141,0	1564	1406				
AL#200026	26	69,9	198,0	141,0	1691	-				_
AL#200028	28	74,7	198,0	141,0	1820	_				_
AL#200030	30	79,5	198,0	141,0	1853	_				_

